

SAFETY DATA SHEET

Revision Date 16-Jul-2015

Version 4

	1. IDENTIFICATION
Product Name	Reagent Alcohol, 80%
Product Code	1202
Recommended Use	For laboratory, scientific, R&D or manufacturing use.
Company	E K Industries, Inc. 1403 Herkimer St. Joliet, IL 60432 Tel. (800) 283-4244
Emergency Telephone	Call CHÉMTREC 1-800-424-9300 (EKI CCN 7453)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Specific target organ toxicity (single exposure)	Category 1
Flammable liquids	Category 2

Label elements

Signal word Danger

Hazard statements

Harmful if swallowed. Causes damage to organs. Highly flammable liquid and vapor.



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth. In case of fire: Use CO2, dry chemical, or foam for extinction.

Precautionary Statements - Storage

Store locked up. Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Ethyl alcohol	64-17-5	65-75
Water	7732-18-5	20
Methyl alcohol	67-56-1	2-4
Isopropyl alcohol	67-63-0	2-4

4. FIRST AID MEASURES

Description of first aid measures

Eye contact	Immediately flush with plenty of water for at least 15 minutes, separating eyelids occasionally. Remove contact lenses if present. Get immediate medical attention.	
Skin contact	Wash thoroughly with soap and water while removing contaminated garments. Get medical attention if irritation develops. Wash contaminated clothing before reuse.	
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.	
Ingestion	Do NOT induce vomiting unless instructed to do so by medical personnel. If conscious, rinse mouth and give several glasses of water to drink. Never give anything by mouth to an unconscious person. Get immediate medical attention.	
Most important symptoms and effects, both acute and delayed		
-		

SymptomsIf swallowed or inhaled, causes irritation. Intoxicant. May cause headache, drowsiness,
nausea, vomiting, blurred vision, blindness, coma, and death.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

In case of fire, use water fog, dry chemical, CO2 or "alcohol resistant" foam

Specific hazards arising from the chemical

Vapors can flow along surfaces to distant ignition sources and flash back.

Protective equipment and precautions for firefighters

Firefighters should wear self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode.

NFPA_	Health hazards 2	Flammability 3	Instability 0	Physical and Chemical Properties -
				•

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures				
Personal precautions	Remove all sources of ignition. Use personal protective equipment as required. Ensure adequate ventilation, especially in confined areas. Evacuate personnel to safe areas. Avoid contact with skin, eyes and inhalation of vapors.			
Environmental precautions	Do not allow into any sewer, on the ground or into any body of water. Avoid release to the environment.			
Methods and material for containm	ent and cleaning up			
Methods for containment Prevent further leakage or spillage if safe to do so.				
Absorb spill with inert material, scoop up and containerize for disposal. Take precautionary measures against static discharges.				
	7. HANDLING AND STORAGE			
Precautions for safe handling Advice on safe handling	7. HANDLING AND STORAGE Use personal protective equipment as required Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.			
	Use personal protective equipment as required Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Avoid			
Advice on safe handling	Use personal protective equipment as required Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Keep container tightly closed in a dry and well-ventilated place. Store in an approved			

Occupational exposure limits

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m³
Methyl alcohol 67-56-1	STEL: 250 ppm TWA: 200 ppm Skin	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) Skin	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³

Appropriate engineering controls

Engineering Controls Emergency showers, eyewash stations, ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles.
Skin and body protection	Wear fire/flame resistant/retardant clothing. Wear protective gloves and protective clothing.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be

required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Odor Odor threshold	Liquid Clear, colorless Odor of grain alcohol No information available
рН	No information available
Melting point / freezing point	No information available
Boiling point / boiling range	No information available
Flash point	20 C approx.
Evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor pressure	No information available
Vapor density	No information available
Relative density	No information available
Water solubility	Miscible with water
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Conditions to avoid	Sources of ignition
Incompatible materials	Strong oxidizing agents. Alkaline substances. Ammonia.

Hazardous Decomposition Products None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Ethyl alcohol	-
Chemical Name	Oral LD50
Ingestion	No data available.
Skin contact	No data available.
Eye contact	No data available.
Inhalation	No data available.

Dermal LD50

Inhalation LC50 = 124.7 mg/L (Rat) 4 h

64-17-5			
Methyl alcohol 67-56-1	= 5628 mg/kg (Rat)	-	= 83.2 mg/L (Rat)4 h
Isopropyl alcohol 67-63-0	= 4396 mg/kg (Rat)	= 12800 mg/kg (Rabbit)	= 16000 ppm (Rat)8 h

Information on toxicological effects

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	,	May cause irritation and dryness. Repeated exposure may cause dermatitis. Harmful if absorbed through skin.			
Serious eye damage/eye	irritation Irritating to e	Irritating to eyes.			
Sensitization	No information	No information available.			
Germ cell mutagenicity	No information	No information available.			
Carcinogenicity	The table be	The table below indicates whether each agency has listed any ingredient as a carcinogen			
Chemical Name	ACGIH	CGIH IARC NTP OSHA			
Isopropyl alcohol 67-63-0	-	- Group 3			
IARC (International Agency for Research on Cancer)					

Group 3 - Not classifiable as to carcinogenicity in humans

STOT - single exposure Eyes, Skin, Respiratory system, Central nervous system, Liver, Reproductive System,

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Ethyl alcohol 64-17-5	-	12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	9268 - 14221: 48 h Daphnia magna mg/L LC50 10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static
Methyl alcohol 67-56-1	-	28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through	_
Isopropyl alcohol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50	13299: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Ethyl alcohol 64-17-5	-0.32
Methyl alcohol 67-56-1	-0.77
Isopropyl alcohol 67-63-0	0.05

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and
	regulations.

Contaminated packaging Do not reuse container. Emptied containers may contain residue. Continue to follow label warnings after container is emptied.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl alcohol	-	Included in waste stream:	-	U154
67-56-1		F039		

Chemical Name	California Hazardous Waste Status	
Ethyl alcohol	Toxic	
64-17-5	Ignitable	
Methyl alcohol	Toxic	
67-56-1	Ignitable	
Isopropyl alcohol	Toxic	
67-63-0	Ignitable	

14. TRANSPORT INFORMATION

Transportation information is provided as a general reference only and may not be applicable in all situations. This information applies to non-bulk shipments only. Per 49 CFR §173.22, it is the shipper's responsibility to ensure that all materials are properly packaged, classified and labeled prior to shipment.

DOT

UN/ID no.	UN 1170
Proper shipping name	Ethanol
Hazard Class	3
Packing Group	II
<u>IATA</u> UN/ID no. Proper shipping name Hazard Class Packing Group	UN 1170 Ethanol 3 II

15. REGULATORY INFORMATION

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Methyl alcohol - 67-56-1	1.0
Isopropyl alcohol - 67-63-0	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methyl alcohol	5000 lb	-	RQ 5000 lb final RQ
67-56-1			RQ 2270 kg final RQ
UC Otata Danulatiana			

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Ethyl alcohol - 64-17-5	Carcinogen Developmental
Methyl alcohol - 67-56-1	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ethyl alcohol 64-17-5	Х	X	Х
Methyl alcohol 67-56-1	Х	X	Х
Isopropyl alcohol 67-63-0	Х	X	Х

16. OTHER INFORMATION

Prepared By Revision Date <u>Disclaimer</u> EKI Regulatory Affairs (Email: reg@eki-chem.com) 16-Jul-2015

E K Industries, Inc. makes no representation as to the comprehensiveness or accuracy of this document. Individuals using this information, or the product to which it refers, must exercise their independent judgment in determining all appropriateness for a particular purpose. Accordingly, E K Industries, Inc. will not be responsible for damages of any kind or nature resulting from the use of this information or the corresponding product. No representations or warranties of any kind or nature, including but not limited to: express warranties, implied warranties or merchantability, or warranties of fitness for a particular purpose, are made hereunder with respect to the information set forth herein or to the product to which the information refers.

End of Safety Data Sheet